UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/613,628	07/02/2003	Varadarajan Srinivasan	NLMI.P211	4351

25670   7590   05/18/2007
WILLIAM L. PARADICE, III
4880 STEVENS CREEK BOULEVARD
SUITE 201
SAN JOSE, CA 95129

EXAMINER
WU, JIANYE

ART UNIT	PAPER NUMBER
2609	

MAIL DATE	DELIVERY MODE
05/18/2007	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

PTOL-90A (Rev. 04/07)

	Office Action Summary	Application No.	Applicant(s)
		10/613,628	SRINIVASAN ET AL.
		Examiner	**Art Unit**	
		Jianye Wu	2609	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE _3_ MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.
- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133).
  Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

1) ☒ Responsive to communication(s) filed on _03 April 2007_.

2a) ☒ This action is **FINAL**. 2b) ☐ This action is non-final.

3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

4) ☒ Claim(s) _1-24_ is/are pending in the application.

   4a) Of the above claim(s) _____ is/are withdrawn from consideration.

5) ☐ Claim(s) _____ is/are allowed.

6) ☒ Claim(s) _1-24_ is/are rejected.

7) ☐ Claim(s) _____ is/are objected to.

8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

9) ☐ The specification is objected to by the Examiner.

10) ☒ The drawing(s) filed on _____ is/are: a)☒ accepted or b)☐ objected to by the Examiner.

   Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).

   Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).

11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).

   a)☐ All b)☐ Some * c)☐ None of:

   1.☐ Certified copies of the priority documents have been received.

   2.☐ Certified copies of the priority documents have been received in Application No. _____.

   3.☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

   * See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

1) ☒ Notice of References Cited (PTO-892)

2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)

3) ☐ Information Disclosure Statement(s) (PTO/SB/08)
   Paper No(s)/Mail Date _____.

4) ☐ Interview Summary (PTO-413)
   Paper No(s)/Mail Date. _____.

5) ☐ Notice of Informal Patent Application

6) ☐ Other: _____.

DETAILED ACTION

Claim Rejections - 35 USC § 102

1.   The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that

form the basis for the rejections under this section made in this Office action:

> A person shall be entitled to a patent unless –
>
> (b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.

2.   **Claim 1, 3,** and **15** are rejected under 35 U.S.C. 102(b) as being anticipated by

Blake et al, "An Architecture for Differentiated Services", RFC 2475, December, 1998,

herein after being referenced as **Blake.**

For **Claim 1**, Blake discloses a traffic management processor (Figure 1, page 16)

for independently throttling the bandwidth of individual traffic flows, comprising:

an instruction decoder (Classifier in Figure 1, page 16), having an input to

receive a throttle control instruction identifying a flow identification ID (DS codepoint,

3rd bullet in page 3, or page 4) of a particular traffic flow to be throttled, and having an

output (the output from Classifier to Meter in Figure 1, Page 16) to provide a throttle

enable signal; and

a departure time calculator circuit (the combination of Meter and Marker in Figure

1, Page 16) having an input to receive the throttle enable signal (the input from Marker

to Shaper/Dropper in Figure 1, Page 16) and configured to calculate a departure time

(Shaper/Dropper in Figure 1, Page 16) for the incoming packet in response to size and

bandwidth parameters associated with the incoming (Metering, page 6).

As to **claim 3**, Blake discloses the traffic management processor of Claim 1 (as applied to claim 1 above), wherein the throttle control instruction further comprises a specified traffic type indicator (DS codepoint in page 4) that indicates which type of traffic is be throttled.

For **claim 15**, Blake discloses a method for selectively throttling any number of traffic flows, comprising:

receiving an incoming packet including a flow ID (DS codepoint in page 4), the flow ID indicating to which traffic flow the incoming packet belongs;

receiving a throttle control instruction (the output of Marker in Figure 1, page 16) including a specified flow ID indicating which traffic flow is subject to throttling;

comparing the specified flow ID with the incoming packet's ID to generate a throttle enable signal (the output from Classifier to Meter in Figure 1, page 16); and

selectively delaying transmission of the incoming packet in response to the throttle enable signal (the output from Marker in Figure 1, page 16).

3.   **Claim 9-10** and **12-14** are rejected under 35 U.S.C. 102(b) as being anticipated by Heinanen et al, "A Single Rate Three Color Marker", RFC 2697, September 1999 (herein af **Heinanen**).

For **claim 9**, Heinanen discloses a method for selectively throttling (function of Marker, Figure in Page 2), individual traffic flows, comprising:

receiving an incoming packet including a BMF and a flow ID (DS field, second paragraph from the bottom of Section 1, page 2, both BMF and ID are interpreted as independent numbers to be stored in DS which has space to hold more than one

number), the flow ID (color of packet, second paragraph from the bottom of Section 1,

page 2), indicating to which traffic flow the incoming packet;

receiving a throttle control instruction field (Result, the Figure in page 2)

specifying which traffic flow is subject to throttling;

determining whether the incoming packet is part of the traffic flow specified by

the throttle control instruction (Color-Aware procedure, last set of bullets in page 3); and

selectively delaying transmission of the incoming packet in response to the

determining (Color-Aware procedure, last set of bullets in page 3).

As to **claim 10**, the method of Claim 9 (as applied to claim 9 above), wherein the

determining comprises: comparing a specified flow ID (color of packet, second

paragraph from the bottom of Section 1, page 2) provided by the throttle control

instruction with the flow ID from the incoming packet (Color-Aware procedure, last set of

bullets in page 3).

As to **claim 12**, Heinanen discloses the method of Claim 9 (as applied to claim 9

above), wherein the throttle control instruction further specifies which types of traffic are

subject to throttling (Color-Aware procedure, last set of bullets in page 3).

As to **claim 13**, Heinanen discloses the method of Claim 12 (as applied to claim

12 above), further comprising:

ascertaining whether the incoming packet is of the traffic type specified in

the throttle control instruction (Color-Aware procedure, last set of bullets in page 3).

As to **claim 14**, Heinanen discloses the method of Claim 13 (as applied to

claim 13 above), wherein the ascertaining comprises:

comparing a traffic type indicator specified by the throttle control instruction with

a traffic type indicator corresponding to the incoming packet.

Claim Rejections - 35 USC § 103

4.   The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all

obviousness rejections set forth in this Office action:

> (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

The factual inquiries set forth in Graham v. John Deere Co., 383 U.S. 1, 148

USPQ 459 (1966), that are applied for establishing a background for determining

obviousness under 35 U.S.C. 103(a) are summarized as follows:

> 1. Determining the scope and contents of the prior art.
> 2. Ascertaining the differences between the prior art and the claims at issue.
> 3. Resolving the level of ordinary skill in the pertinent art.
> 4. Considering objective evidence present in the application indicating obviousness or nonobviousness.

5.   Claim **2, 4-7,** and **27** are rejected under 35 U.S.C. 103(a) as being unpatentable

over Blake et al, "An Architecture for Differentiated Services", RFC 2475, December,

1998 in view of Heinanen et al, "A Single Rate Three Color Marker", RFC 2697,

September 1999.

As to **claim 2**, it is based on claim 1, wherein DTC circuit is configured to

calculate departure time of incoming packets by selectively multiplying a BMF.

Blake discloses everything in claim 1, but fails to teach specific way of metering

(deciding departure time for each packet), including selectively using BMF to calculate

departure time of packets.

Heinanen discloses a way of metering (srTCM in Color-Aware mode, 3rd

paragraph from the bottom in page 3) an incoming packet based on bandwidth

parameters CIR, CBS, EBS (Abstract Section in page 1) and the color of the packet

(First paragraph of Section 1 in page 1). The departure time of outgoing packet is then

adjusted according to the color of the packet. This is equivalent to multiplying a BWF in

that the departure time of packet is adjusted. Following the engineering design

expedient, the colored traffic can either be put in different transmit queues, or put on a

single transmit queue with departure time being adjust by multiplying different factors

(such as 1, 2, and 3) for traffic with different colors.

Blake is explicitly cited as one of the references (Last reference in Page 6) in

Heinanen because Heinanen is written under the framework taught by Blake for easy

implementation.

Therefore, it would have been obvious to a person of ordinary skill in the art at

the time of the invention to combine Blake with Heinanen because Heinanen is written

under the framework taught by Blake for easy implementation.

As to **claim 4**, Heinanen further discloses the traffic management processor of

Claim 3, wherein throttle control instruction further comprises a mode signal (mode

which can be Color-Blind or Color-Aware, second paragraph of page 3) that can be set

to a state that causes the DTC circuit to alter the packer's departure time, regardless of

the packet's flow ID or traffic type (Color-Blind mode, page 3).

The combination of Blake and Heinanen taught everything in claim 3, Heinanen

further discloses additional embodiments in claim 4 as described above.

Blake is explicitly cited as one of the references (Last reference in Page 6) in Heinanen because Heinanen is written under the framework taught by Blake for easy implementation.

Therefore, it would have been obvious to a person of ordinary skill in the art at the time of the invention to combine Blake with Heinanen because Heinanen is written under the framework taught by Blake for easy implementation.

As to **claim 5**, the traffic management processor of Claim 1, further comprising a departure time table coupled to the DTC circuit and having a plurality of rows, each for storing the departure time of a corresponding packet;

Blake discloses everything in claim 1, but fails to explicitly teach the departure time table structure.

However, the outgoing packets that cannot be transmit right away are put on a queue associated with marker (3rd paragraph of Section 2.3.2, page 15 of Blake et al) that is drained in at the rate of physical transmit channel. The transmit queue associated with marker is equivalent to the departure time table coupled to the DTC circuit, and packets on the queue are corresponding to rows of the departure time table, with their positions on the queue equivalent to the departure time of the corresponding packets.

Therefore, it would have been obvious to a person of ordinary skill in the art at the time of the invention to use the traffic management processor comprising a table for departure time because that the transmit queue associated with marker is equivalent to the departure time table coupled to the DTC circuit, and packets on the queue are

corresponding to rows of the departure time table, with their positions on the queue

equivalent to the departure time of the corresponding packets.

For **claim 6**, Blake discloses a traffic management processor comprising: an

instruction decoder (Classifier in Figure 1, page 15) for receiving a throttle control

instruction that specifies which traffic flows are to be throttled, and having an output to

provide a throttle enable signal (the output from Classifier to Meter in Figure 1, page

15); and a DTC circuit for calculating a departure time for the incoming packet (the

combination of Meter and Marker in Figure 1, page 15).

Blake fails to disclose that DTC calculate a departure time in response to packet

size and bandwidth parameters associated, as well as using BMF.

Heinanen discloses a way of metering (srTCM in Color-Aware mode, 3rd

paragraph from the bottom in page 3) an incoming packet based on on its size (packet

of size B, 3rd paragraph from bottom in page 3) and bandwidth parameters (Tc and Te,

second paragraph in page 3, and CIR, CBS, and EBS, Abstract Section in page 1) and

the color of the packet (First paragraph of Section 1 in page 1). The departure time of

outgoing packet is then adjusted according to the color of the packet. This is equivalent

to multiplying a BWF in that the departure time of packet is adjusted. Following the

engineering design expedient, the colored traffic can either be put in different transmit

queues, or put on a single transmit queue with departure time being adjust by

multiplying different factors (such as 1, 2, and 3) for traffic with different colors

Blake is explicitly cited as one of the references (Last reference in Page 6) in Heinanen because Heinanen is written under the framework taught by Blake for easy implementation.

Therefore, it would have been obvious to a person of ordinary skill in the art at the time of the invention to combine Blake with Heinanen because Heinanen is written under the framework taught by Blake for easy implementation.

As to **claim 7**, the traffic management processor of Claim 6, wherein packet includes a flow identification identifying the packet's traffic flow.

The combination of Blake and Heinanen disclose the traffic management processor of Claim 6 (as applied to claim 6 above), Blake further discloses a flow identification identifying the packet's traffic flow (DS codepoint in page 4).

Blake is explicitly cited as one of the references (Last reference in Page 6) in Heinanen because Heinanen is written under the framework taught by Blake for easy implementation.

Therefore, it would have been obvious to a person of ordinary skill in the art at the time of the invention to combine Blake with Heinanen because Heinanen is written under the framework taught by Blake for easy implementation.

As to **claim 8**, the traffic management processor of Claim 6, wherein the throttle control instruction specifies which types of traffic are to be throttled.

The combination of Blake and Heinanen disclose the traffic management processor of Claim 6 (as applied to claim 6 above), Blake further discloses a flow identification identifying the packet's traffic flow (DS codepoint in page 4).

Blake is explicitly cited as one of the references (Last reference in Page 6) in Heinanen because Heinanen is written under the framework taught by Blake for easy implementation.

Therefore, it would have been obvious to a person of ordinary skill in the art at the time of the invention to combine Blake with Heinanen because Heinanen is written under the framework taught by Blake for easy implementation.

As to **claim 11**, Heinanen discloses the method of Claim 9 (as applied to claim 9 above), wherein the selectively delaying comprises:

receiving packet size (packet of size B, 3rd paragraph from bottom in page 3) and bandwidth parameters for the incoming packet (Tc and Te, second paragraph in page 3, and CIR, CBS, and EBS, Abstract Section in page 1); and

calculating a departure time for the incoming packet in response to the size and bandwidth parameters (Color-Aware procedure, last set of bullets in page 3).

Heinanen fails to explicitly disclose selectively multiplying the bandwidth parameter by the BMF in response to the determining;

Heinanen discloses a way of metering (srTCM in Color-Aware mode, 3rd paragraph from the bottom in page 3) an incoming packet based on bandwidth parameters and the color of the packet (First paragraph of Section 1 in page 1). The departure time of outgoing packet is then adjusted according to the color of the packet. This is equivalent to multiplying a BWF in that the departure time of packet is adjusted. Following the engineering design expedient, the colored traffic can either be put in

different transmit queues, or put on a single transmit queue with departure time being adjust by multiplying different factors (such as 1, 2, and 3) for traffic with different colors.

Therefore, it would have been obvious to a person of ordinary skill in the art at the time of the invention to selectively multiplying the departure time by the BMF because of engineering design expedient.

As to **claim 16**, Blake discloses everything in the method of Claim 15 (as applied to claim 15 above), but fails to disclose calculating a departure time for the incoming packet in response to size and bandwidth parameters corresponding to the incoming packet, wherein the bandwidth parameter is selectively multiplied by a BMF.

Heinanen discloses a way of metering (srTCM in Color-Aware mode, 3rd paragraph from the bottom in page 3) an incoming packet based on bandwidth parameters CIR, CBS, EBS (Abstract Section in page 1) and the color of the packet (First paragraph of Section 1 in page 1). The departure time of outgoing packet is then adjusted according to the color of the packet. This is equivalent to multiplying a BWF in that the departure time of packet is adjusted. Following the engineering design expedient, the colored traffic can either be put in different transmit queues, or put on a single transmit queue with departure time being adjust by multiplying different factors (such as 1, 2, and 3) for traffic with different colors.

Blake is explicitly cited as one of the references (Last reference in Page 6) in Heinanen because Heinanen is written under the framework taught by Blake for easy implementation.

Therefore, it would have been obvious to a person of ordinary skill in the art at the time of the invention to combine Blake with Heinanen because Heinanen is written under the framework taught by Blake for easy implementation.

As to **claim 17**, the method of Claim 16, wherein the throttle control instruction further specifies which types of traffic are subject to throttling.

The combination of Blake and Heinanen disclose everything in the method of Claim 16 (as applied to claim 16 above), Heinanen further discloses the throttle control instruction further specifies which types of traffic (colors of packets, second paragraph from the bottom of Section 1, page 2) are subject to throttling.

Heinanen is disclosed within the framework taught by Blake et al, which is explicitly cited as one of the references in Heinanen et al.

Therefore, it would have been obvious to a person of ordinary skill in the art at the time of the invention to combine Blake with Heinanen because Blake is explicitly cited as one of the references in Heinanen et al.

As to **claim 18**, the combination of Blake and Heinanen disclose everything in the method of Claim 17 (as applied to claim 17 above). Heinanen further discloses that in the method of Claim 17:

determining whether the incoming packet is of the traffic type (color of the packet, second paragraph from the bottom of Section 1, page 2) specified by the throttle control instruction; and

selectively asserting the throttle enable signal in to the determining (Color-Aware procedure, last set of bullets in page 3).

Blake is explicitly cited as one of the references (Last reference in Page 6) in

Heinanen because Heinanen is written under the framework taught by Blake for easy

implementation.

Therefore, it would have been obvious to a person of ordinary skill in the art at

the time of the invention to combine Blake with Heinanen because Heinanen is written

under the framework taught by Blake for easy implementation.

As to **claim 19**, tBlake and Heinanen in combination the traffic management

processor of Claim 2, wherein each packet includes the BMF and the flow ID (DS field,

second paragraph from the bottom of Section 1, page 2, both BMF and ID are

interpreted as independent numbers to be stored in DS which has space to hold more

than one number).

As to **claim 22**, Blake and Heinanen in combination disclose traffic management

processor of Claim 6, Blake further disclose wherein each packet includes the BMF (DS

field, second paragraph from the bottom of Section 1, page 2, both BMF and ID are

interpreted as independent numbers to be stored in DS which has space to hold more

than one number).

6.   **Claims 20-21** and **23-24** are rejected under 35 U.S.C. 103(a) as being

unpatentable over Blake in view of Ohgane et al, US Patent 587173 with the title

"Communication Control Device and Method for use in an ATM System Operable in an

ABR Mode", Feb. 23, 1999 (hereinafter **Ohgane**).

As to **Claim 20**, Blake and Heinanen in combination disclose the traffic

management processor of Claim 1;

they are silent on a CAM device; ·

Ohgane discloses a CAM device having a plurality of rows (FIG.6, and last paragraph of Col 8), each for storing the flow ID for a corresponding packet (VC, last paragraph of Col 8);

The memory device can be implemented in CAM (the combination of 25 and 27 of FIG. 1), which is often used in network devices to improve performance. In addition, implementing methods/algorithms in hardware memory devices (such as CAM) is conventional in the art and this examiner takes Office Notice of this notion. The advantages of this include great improvement of performance and reliability.

Therefore, it would have been obvious to a person of ordinary skill in the art at the time of the invention to combine Blake with Ohgane to produce a system implementing methods taught by Blake with memory devices disclosed by Ohgane because of the performance improvement and reliability.

As to **Claim 21**, Blake, Heinanen and Ohgane disclose the traffic management processor of Claim 20; Ohgane further discloses wherein each row (FIG.6, and last paragraph of Col 8) of the CAM device further stores a traffic type indicator TTI (ATM cell header shown in Fig. 6 which inherently has a field payload type field PT) indicating a traffic type of the corresponding packet (VC, last paragraph of Col 8).

7.   Claims **23-24** are rejected under 35 U.S.C. 103(a) as being unpatentable over Blake and Heinanen as applied to claim 7 above, and further in view of Ohgane.

As to **Claim 23**, Blake and Heinanen in combination disclose the traffic management processor of Claim 7;

they are silent on a CAM device;

Ohgane discloses a CAM device (the combination of 25 and 27 of FIG. 1) having

a plurality of rows (FIG.6, and last paragraph of Col 8), each for storing the flow ID for a

corresponding packet (VC, last paragraph of Col 8);

The memory device can be implemented in CAM, which is often used in network

devices to improve performance. In addition, implementing methods/algorithms in

hardware memory devices (such as CAM) is conventional in the art and this examiner

takes Office Notice of this notion. The advantages of this include great improvement of

performance and reliability.

Therefore, it would have been obvious to a person of ordinary skill in the

art at the time of the invention to combine Blake with Ohgane to produce a system

implementing methods taught by Blake with memory devices disclosed by Ohgane

because of the performance improvement and reliability.

As to **Claim 24**, Blake, Heinanen and Ohgane disclose the traffic management

processor of Claim 23; Ohgane further discloses wherein each row (FIG.6, and last

paragraph of Col 8) of the CAM device further stores a traffic type indicator TTI (ATM

cell header shown in Fig. 6 which inherently has a field payload type field PT) indicating

a traffic type of the corresponding packet (VC, last paragraph of Col 8).

Response to Arguments/Remarks

8.   Applicant's arguments filed on 4/03/2007 have been fully considered but they are

not persuasive.

9.   For remarks on claims 1-5 (from Line 15 of Page 8 to Line 13 of Page 10),

particularly representative claim 1, Applicants argue that "Blake fails to disclose or

suggest a traffic management processor including 'an instruction decoder having an

input to receive a throttle control instruction identifying a flow identification ID of a

particular traffic flow to be throttled, and having an output to provide a throttle enable

signal'" (Lines 6 to 9 of Page 10) because the following reasons:

      a) a traffic flow in the application is different from the type of traffic disclosed by

Blake which applicants interpret as an aggregation of multiple traffic flows. (Lines 4-13,

particularly 6 of Page 9);

      b) "Blake's classifier is not an instruction decoder, does not have an input to

receive a throttle control instruction and does not have an output to generate a throttle

enable signal" (Lines 21-23 of Page 9);

      In response, Examiner respectfully disagrees. According to MPEP claims should

be given "the broadest reasonable interpretation" (Bullet 2 of H Subsection in MPEP

708(a)). The following are Examiner's responses to applicants' comments:

      a) What Blake disclose for the packets belong to a traffic type is a set of packets

that have the same ID (a part of DS codepoint); upon which the same set of rules will be

applied when being processed (scheduled), which conceptually is exactly the same as

the packets belong to a traffic flow as described in the application. Applicants seem to

interpret a traffic type narrowly only as the aggregation of multiple traffic flows.

However, a traffic type can easily be interpreted as having only one traffic flow and is

therefore identical to a traffic flow;

b) Blake's classifier reads traffic type ID (or code, a part of DS codepoint) of

every packet and determines (decodes) its value and then inform (sending signal) to

other one or more of other components of the traffic management processor for

different actions (including throttling), with the traffic code of each packet being the

instruction code. It matches very well with the structure and functions of the decoder

disclosed by the application. The logic of the classifier on how to interpret traffic code

can either be pre-built in or through the configuration of its parameters that can be

changed with configuration instructions; these techniques are common practice in the

art and is known to any person with ordinary skills in the art.

10.   For remarks on claims 15-18 (from Line 25 of Page 10 to Line 22 of Page 12),

particularly representative claim 15, Applicants use the same reasons as those of Claim

1.

In response, the explanation to Claim 1 presented above is applied.

11.   For remarks on claims 9-14 (from Line 5 of Page 12 to Line 4 of Page 14),

particularly representative claim 9, Applicants argue that Heinanen fails to disclose or

suggest the method of Claim 9 due to the following reasons:

a) "color of packet of Heinanen is not equivalent to a flow ID of the application.

(Lines 1-12 of Page 11);

b) Heinanen does not disclose throttle instructions (Lines 20-21 of Page 15); and

c) "Heinanen's 'color aware procedure' does NOT determine 'whether the

incoming packet is part of the traffic flow specified by the throttle control instruction'"

(Lines 21-23 of Page 13);

In response, Examiner respectfully disagrees. The following are Examiner's responses to applicants' remarks:

a) color of packet of Heinanen (a part of DS) is equivalent to BMF, which provides information on how to process the packet for a traffic flow; applicants also have a similar argument regarding traffic flow ID (another part of DS) as applied to claim 1, the explanation to Claims 1 presented above is applied;

b) The output of marker (and part output from meter directly fed into the shaper of the traffic management processor shown in Figure 1 of RFC 2475, as suggested in line 2 of Abstract of Heinanen) suggests traffic control instructions that include throttling instructions because packets with different color will be processed differently;

c) As explained in the Office Action for claim 1, the DS field of each packet including both color (BMF) and traffic flow ID determines whether the packet belongs to the traffic flow and provide throttle control instructions when necessary.

12. For remarks on claims 6-8, 11-14 and 16-18 (from Line 11 of Page 14 to Line 20 of Page 16), particularly representative claim 6, Applicants argue that "Heinanen fails to disclose or suggest the traffic management processor of Applicants' Claim 12." (Lines 7-8 of Page 15) due to the following reasons:

a) failure to disclose to the encoder (Lines 1-12 of Page 11);

b) failure to throttle instructions (Lines 20-21 of Page 15); and

c) failure to DTC (Lines 21-23 of Page 13);

In response, Examiner respectfully disagrees. The following are Examiner's responses to applicants' remarks:

a) an encoder is disclosed as explained in b) of the response to remark on claim

1 above;

b) throttle instructions are disclosed as explained in c) of the response to remark

on claim 9 above;

c) a DTC is disclosed as Shaper in Figure 1 of Blake; the shaper rearranges

departure time of packet to make transmission smooth, which is equivalent to function

of DTC determining departure time for packets.

13.   Applicant arguments with respect to new claims 19-24 have been considered but

are moot in view of the new ground(s) of rejection.

Conclusion

Applicant's amendment necessitated the new ground(s) of rejection presented in

this Office action. Accordingly, **THIS ACTION IS MADE FINAL**. See MPEP

§ 706.07(a). Applicant is reminded of the extension of time policy as set forth in 37

CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE

MONTHS from the mailing date of this action. In the event a first reply is filed within

TWO MONTHS of the mailing date of this final action and the advisory action is not

mailed until after the end of the THREE-MONTH shortened statutory period, then the

shortened statutory period will expire on the date the advisory action is mailed, and any

extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of

the advisory action. In no event, however, will the statutory period for reply expire later

than SIX MONTHS from the date of this final action.

Any inquiry concerning this communication or earlier communications from the

examiner should be directed to Jianye Wu whose telephone number is (571)270-1665.

The examiner can normally be reached on Monday to Friday, 8am to 5pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's

supervisor, Eliseo Ramos-Feliciano can be reached on (571)272-7925. The fax phone

number for the organization where this application or proceeding is assigned is 571-

273-8300.

Information regarding the status of an application may be obtained from the

Patent Application Information Retrieval (PAIR) system. Status information for

published applications may be obtained from either Private PAIR or Public PAIR.

Status information for unpublished applications is available through Private PAIR only.

For more information about the PAIR system, see http://pair-direct.uspto.gov. Should

you have questions on access to the Private PAIR system, contact the Electronic

Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a

USPTO Customer Service Representative or access to the automated information

system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

5-09-07

LANA LE
PRIMARY EXAMINE

Jianye Wu